

What is claimed is:

1. A lens barrel, comprising:

a stationary barrel (17);

5 first (12 and 24), second (11, or 13 and 27), and
third (11, or 13 and 27) lens support rings which are guided
in a direction of an optical axis via said stationary
barrel; and

10 a lens drive ring (23) which is rotated about said
optical axis to move each of said first lens support ring,
said second lens support ring and said third lens support
ring in said optical axis direction;

wherein said lens drive ring comprises:

15 a first extending guide portion (23a) which is
engaged with a fixed extending guide portion (17b) formed
on said stationary barrel to move said lens drive ring
in said optical axis direction upon said lens drive ring
being rotated;

20 an engaging portion (23c) which is engaged with a
guiding portion (24c) formed on said first lens support
ring, so that said lens drive ring and said first lens
support ring are relatively rotatable about said optical
axis and integrally movable in said optical axis
direction;

25 a second extending guide portion (23b or 23f), which
is engaged with an extending guide portion (11a or 27a)

Sub A1 }
formed on said second lens support ring, to move said second lens support ring in said optical axis direction relative to said lens drive ring via rotation of said lens drive ring; and

5 a third extending guide portion (23f or 23b) which is engaged with an extending guide portion (27a or 11a) formed on said third lens support ring to move said third lens support ring in said optical axis direction relative to said lens drive ring by said rotation of said lens drive
10 ring.

2. The lens barrel according to claim 1, wherein said lens drive ring is molded with synthetic resin, and wherein said engaging portion of said lens drive ring, said first extending guide portion, said second
15 extending guide portion, and said third extending guide portion, are formed integral with said lens drive ring.

3. The lens barrel according to claim 1, wherein said engaging portion of said lens drive ring, said first extending guide portion, said second extending guide
20 portion, and said third extending guide portion are all formed as projections that project from said lens drive ring.

4. The lens barrel according to claim 1, wherein said second extending guide portion and said third
25 extending guide portion are formed on one and the other

of inner and outer peripheral surfaces of said lens drive ring, respectively.

Sub
A2 5 5. The lens barrel according to claim 1, wherein said lens drive ring comprises a rotational transfer recess (23d) to receive a driving force by which said lens drive ring rotates.

10 6. The lens barrel according to claim 1, wherein said stationary barrel comprises a linear guide portion (17c and 17f) for guiding one of said first lens support ring, and said second and third lens support rings in said optical axis direction; and

15 wherein said first lens support ring comprises linear guide portion (24b) for guiding the other of said first lens support ring, and said second and third lens support rings in said optical axis direction.

7. The lens barrel according to claim 1, further comprising:

20 a rotating ring (29) supported by one of said second lens support ring and said third lens support ring to be rotatable about said optical axis; and

25 a fourth lens support ring (14) which is guided in said optical axis direction without rotating about said optical axis, said fourth lens support ring being moved in said optical axis direction via rotation of said rotating ring;

wherein said lens drive ring includes a lever (28) via which said rotation of said lens drive ring is transferred to said rotating ring.

8. A lens barrel having a first lens group (L3) and a second lens group (L4) which are movable in a direction of an optical axis relative to each other, said lens barrel comprising:

a first lens support ring (13) which supports said first lens group;

a rotating ring (29) which is supported by said first lens support ring to be rotatable about said optical axis, wherein said rotating ring is rotated about said optical axis;

a second lens support ring (14) which holds said second lens group, and is positioned between an inner peripheral surface of said rotating ring and an outer peripheral surface of said first lens support ring;

a linear guide bottomed groove (14a) formed on one of an outer peripheral surface of said first lens support ring and an inner peripheral surface of said second lens support ring to extend parallel to said optical axis;

a linear guide projection (13a) formed on the other of said outer peripheral surface of said first lens support ring and said inner peripheral surface of said second lens support ring to be slidably engaged in said

linear guide bottomed groove;

5 a extending guide protrusion (29b) formed on one of
an inner peripheral surface of said rotating ring and an
outer peripheral surface of said second lens support ring;

and

10 a follower pin (14b) formed on the other of said
inner peripheral surface of said rotating ring and said
outer peripheral surface of said second lens support ring,
said follower pin engaging with said extending guide
protrusion;

wherein each of said first lens support ring, said
second lens support ring, and said rotating ring is formed
as a solid annular member having no radial through holes.

9. The lens barrel according to claim 8, wherein
15 said extending guide protrusion (29b) has a rectangular
shape in cross section; and

20 wherein said follower pin (14b) comprises at least
one pair of cylindrical follower pins, each said pair of
cylindrical follower pins holding a corresponding said
extending guide protrusion therebetween.

10. The lens barrel according to claim 8, wherein
said follower pin comes into linear contact with said
extending guide protrusion (29b) along a line extending
substantially in a radial direction of said lens barrel.

25 11. The lens barrel according to claim 8, wherein

SUB
A2

each said extending guide protrusion (29b) comprises a non-linear contour.

12. The lens barrel according to claim 8, wherein each of said first lens support ring, said second lens support ring, and said rotating ring is molded with synthetic resin.

SUB
A3

13. The lens barrel according to claim 8, wherein said extending guide protrusion (29b) is formed integral with one of said rotating ring and said second lens support ring, and wherein said follower pin (14b) is formed on the other of said rotating ring and said second lens support ring.

14. The lens barrel according to claim 8, wherein said linear guide projection (13a) is formed integral with one of said first lens support ring and said second lens support ring.

15. The lens barrel according to claim 8, wherein one of said first lens support ring and said rotating ring comprises a circumferential bottomed groove (13b) which extends circumferentially;

wherein said the other of said first lens support ring and said rotating ring comprises a guide projection (29a) which is engaged in said circumferential bottomed groove; and

25 wherein said first lens support ring and said

SUB
A3

rotating ring are coupled to each other to be rotatable relative to each other due to an engagement of said guide projection with said circumferential bottomed groove.

16. The lens barrel according to claim 8, wherein
5 each of said first lens group and said second lens group serves a lens group of a zoom lens system.

SUB
A4

17. The lens barrel according to claim 16, further comprising:

10 a third lens group (L1 or L2) which differs from said first and second lens groups;

a zoom ring (19) which can be manually rotated;

a cam ring (23) which is rotated by rotation of said zoom ring to move said third lens group in said optical axis direction; and

15 a rotational transfer arm (29c) which extends from said rotating ring and is engaged with said cam ring to receive a rotational force from said cam ring;

wherein a rotation of said zoom ring causes said rotating ring to rotate to thereby move said first lens
20 group and second lens group in said optical axis direction relative to each other.

18. A lens barrel having a first lens group (L2) and a second lens group (L1) which are relatively movable in a direction of the optical axis thereof, said lens
25 barrel comprising:

a stationary barrel (17);

SUB
A4
a drive ring (23) which is supported by said stationary barrel to move in said optical axis direction while rotating about said optical axis relative to said stationary barrel upon being rotated;

10 a first movable ring (12 and 24) which supports said first lens group (L2) and is guided along said optical axis, said first movable ring being supported by said drive ring so that said drive ring is rotatable about said optical axis and integrally movable with said first movable ring in said optical axis direction; and

15 a second movable ring (11) which supports said second lens group (L1) and is guided in said optical axis direction without rotating about said optical axis, a rotation of said drive ring relative to said second movable ring causing said second movable ring to move in said optical axis direction relative to said drive ring;

20 wherein said first movable ring moves together with said drive ring in said optical axis direction, and at the same time, said second movable ring concurrently moves in said optical axis direction relative to said drive ring when said drive ring moves in said optical axis direction while rotating about said optical axis.

19. The lens barrel according to claim 18, wherein
25 said first movable ring comprises:

SUB
A4

a lens support ring (12) which supports said first lens group, and is positioned in said linear moving ring to be supported thereby so that said lens support ring can be moved in the optical axis direction with respect to said linear moving ring while rotating about said optical axis relative to said linear moving ring;

wherein when said linear moving ring is moved forward and rearward in the optical axis direction, said lens support ring integrally moves forward and rearward together with said linear moving ring in said optical axis direction; and

wherein when said lens support is individually rotated, said lens support ring moves forward and rearward in said optical axis direction relative to said linear moving ring.

20. The lens barrel according to claim 18, wherein said first movable ring is guided by said stationary barrel so as to be movable in said optical axis direction

without rotating about said optical axis; and

wherein said second movable ring is guided by said first movable ring to be movable in said optical axis direction without rotating about said optical axis.

5 21. The lens barrel according to claim 20, wherein said stationary barrel comprises a first linear guide portion (17c) which extends in said optical axis direction;

10 wherein said second movable ring comprises a second linear guide portion (11b) which extends in said optical axis direction;

 wherein said first movable ring comprises:

15 a first linear guide projection (24a) which extends parallel to said optical axis, and is engaged with said first linear guide portion (17c) to guide said first movable ring in said optical axis direction without rotating said first movable ring about said optical axis; and

20 a second linear guide projection (24b) which extends parallel to said optical axis, and is engaged with said second linear guide portion (11b) to guide said second movable ring in said optical axis direction without rotating said second movable ring about said optical axis;

25 wherein said first linear guide projection (24a) and said second linear guide projection (24b) are formed on

an outer peripheral surface of said first movable ring at the same position in a circumferential direction thereof and at different positions in said optical axis direction.

5 22. The lens barrel according to claim 18, further comprising:

SUB
A5

10 a rib-shaped extending guide projection (17b) formed on one of inner and outer peripheral surfaces of said stationary barrel to extend in a direction inclined with respect to said optical axis; and

15 a follower projection (23a) formed on one of inner and outer peripheral surfaces of said drive ring to be engaged with said rib-shaped extending guide projection, said drive ring moving in said optical axis direction while rotating about said optical axis relative to said stationary barrel due to an engagement of said rib-shaped extending guide projection with said follower projection.

20 23. The lens barrel according to claim 22, further comprising:

25 a guide projection (23c) which projects radially from one of a first peripheral surface of said drive ring and a second peripheral surface of said first movable ring, said first peripheral surface and said second peripheral surface facing each other; and

a circumferential groove (24c) formed on the other of said first peripheral surface and said second peripheral surface;

wherein said guide projection (23c) is engaged in said circumferential groove (24c), whereby said drive ring is rotatable about said optical axis relative to said first movable ring and integrally movable with said first movable ring in said optical axis direction.

24. The lens barrel according to claim 23, further comprising:

a second rib-shaped extending guide projection (23b) formed on one of inner and outer peripheral surfaces of said drive ring to extend in a direction inclined with respect to both said optical axis and the direction in which said rib-shaped extending guide projection (17b) extends; and

a lead groove (11a) formed on one of inner and outer peripheral surfaces of said second movable ring;

wherein said second rib-shaped extending guide projection (23b) is engaged in said lead groove (11a), whereby said second movable ring moves in said optical axis direction relative to said drive ring when said drive ring is rotated about said optical axis relative to said stationary barrel.

25. A lens barrel comprising:

optical axis direction; and

SUB 7
AS
a lens support ring (12) which supports said first lens group, and is positioned in said linear moving ring to be supported thereby so that said lens support ring
5 can be moved in the optical axis direction with respect to said linear moving ring while rotating about said optical axis relative to said linear moving ring;

10 wherein when said linear moving ring is moved forward and rearward in the optical axis direction, said lens support ring integrally moves forward and rearward together with said linear moving ring in said optical axis direction; and

20 wherein when said lens support is individually rotated, said lens support ring moves forward and rearward in said optical axis direction relative to said linear moving ring.

27. The lens barrel according to claim 25, further comprising:

20 a rib-shaped extending guide projection (17b) formed on one of inner and outer peripheral surfaces of said stationary barrel to extend in a direction inclined with respect to said optical axis; and

25 a follower projection (23a) formed on one of inner and outer peripheral surfaces of said drive ring to be engaged with said rib-shaped extending guide projection,

50B
AS

said drive ring moving in said optical axis direction while rotating about said optical axis relative to said stationary barrel due to an engagement of said rib-shaped extending guide projection with said follower projection.

28. The lens barrel according to claim 25, further comprising:

10 a guide projection (23c) which projects radially from one of a first peripheral surface of said drive ring and a second peripheral surface of said first movable ring, said first peripheral surface and said second peripheral surface facing each other; and

15 a circumferential groove (24c) formed on the other of said first peripheral surface and said second peripheral surface;

20 wherein said guide projection (23c) is engaged in said circumferential groove (24c), whereby said drive ring is rotatable about said optical axis relative to said first movable ring and integrally movable with said first movable ring in said optical axis direction.

29. The lens barrel according to claim 25, further comprising:

a second lens group (L1); and

25 a second movable ring (11) which supports said second lens group (L1), and is guided in said optical axis

direction without rotating about said optical axis;

wherein said first movable ring (12 and 24) holds
said first lens group (L2); and

SUB
AS 7
5 wherein said second movable ring moves in said
optical axis direction relative to said drive ring when
said drive ring rotates about said optical axis relative
to said stationary barrel.

30. The lens barrel according to claim 29, further
comprising:

10 a second rib-shaped extending guide projection
(23b) formed on one of inner and outer peripheral surfaces
of said drive ring to extend in a direction inclined with
respect to both said optical axis and the direction in
which said rib-shaped extending guide projection (17b)
15 extends; and

a lead groove (11a) formed on one of inner and outer
peripheral surfaces of said second movable ring;

wherein said second rib-shaped extending guide
projection (23b) is engaged in said lead groove (11a),
20 whereby said second movable ring moves in said optical
axis direction relative to said drive ring when said drive
ring is rotated about said optical axis relative to said
stationary barrel.

31. The lens barrel according to claim 29, wherein
25 said first movable ring is guided by said stationary

barrel to be movable in said optical axis direction without rotating about said optical axis; and

wherein said second movable ring is guided by said first movable ring to be movable in said optical axis direction without rotating about said optical axis.

32. The lens barrel according to claim 31, wherein said stationary barrel comprises a first linear guide portion (17c) which extends in said optical axis direction;

wherein said second movable ring comprises a second linear guide portion (11b) which extends in said optical axis direction;

wherein said first movable ring comprises:

a first linear guide projection (24a) which extends parallel to said optical axis and is engaged with said first linear guide portion (17c) to guide said first movable ring in said optical axis direction without rotating said first movable ring about said optical axis; and

a second linear guide projection (24b) which extends parallel to said optical axis, and is engaged with said second linear guide portion (11b) to guide said second movable ring in said optical axis direction without rotating said second movable ring about said optical axis;

wherein said first linear guide projection (24a) and

SUB
A6

said second linear guide projection (24b) are formed on an outer peripheral surface of said first movable ring at the same position in a circumferential direction thereof, at different positions in said optical axis direction.

33. A lens barrel comprising:

a stationary barrel (17);

10 a drive ring (23) which is supported by said stationary barrel to move in a direction of an optical axis while rotating about said optical axis relative to said stationary barrel when said drive ring is rotated; and

15 a first movable ring (11) which supports a first lens group (L1) and is guided in said optical axis direction without rotating about said optical axis, a rotation of said drive ring relative to said first movable ring causing said first movable ring to move in said optical axis direction relative to said drive ring;

20 wherein said first movable ring moves in said optical axis direction relative to said drive ring when said drive ring moves in said optical axis direction while being rotated about said optical axis.

34. The lens barrel according to claim 33, further comprising:

25 a rib-shaped extending guide projection (17b)

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000

formed on one of inner and outer peripheral surfaces of said stationary barrel to extend in a direction inclined with respect to said optical axis; and

a follower projection (23a) formed on one of inner and outer peripheral surfaces of said drive ring to be engaged with said rib-shaped extending guide projection, said drive ring moving in said optical axis direction while rotating about said optical axis relative to said stationary barrel due to an engagement of said rib-shaped extending guide projection with said follower projection.

35. The lens barrel according to claim 33, further comprising:

a second rib-shaped extending guide projection (23b) formed on one of inner and outer peripheral surfaces of said drive ring to extend in a direction inclined with respect to both said optical axis and the direction in which said rib-shaped extending guide projection (17b) extends; and

a lead groove (11a) formed on one of inner and outer peripheral surfaces of said first movable ring;

wherein said second rib-shaped extending guide projection (23b) is engaged in said lead groove (11a), whereby said first movable ring moves in said optical axis direction relative to said drive ring when said drive ring

is rotated about said optical axis relative to said stationary barrel.

36. The lens barrel according to claim 33, further comprising:

5 a second lens group (L2); and

a second movable ring (12 and 24) which supports said second lens group (L2) and is guided in said optical axis direction;

10 wherein said first movable ring (11) supports said first lens group (L1); and

15 wherein said second movable ring (12 and 24) is supported by said drive ring so that said drive ring is rotatable about said optical axis relative to said second movable ring and integrally movable with said second movable ring in said optical axis direction.

37. The lens barrel according to claim 33, wherein said second movable ring comprises:

20 a linear moving ring (24) which is guided in said optical axis direction without rotating about said optical axis, said linear moving ring being supported by said drive ring so as to be relatively rotatable with respect to said drive ring about said optical axis, and to be integrally movable with said drive ring in said optical axis direction; and

25 a lens support ring (12) which supports said second

SUB
Pkt

lens group, and is positioned in said linear moving ring to be supported thereby so that said lens support ring can be moved in the optical axis direction with respect to said linear moving ring while rotating about said optical axis relative to said linear moving ring;

wherein when said linear moving ring is moved forward and rearward in the optical axis direction, said lens support ring integrally moves forward and rearward together with said linear moving ring in said optical axis direction; and

wherein when said lens support is individually rotated, said lens support ring moves forward and rearward in said optical axis direction relative to said linear moving ring.

38. The lens barrel according to claim 36, further comprising:

a guide projection (23c) which projects radially from one of a first peripheral surface of said drive ring and a second peripheral surface of said second movable ring, said first peripheral surface and said second peripheral surface facing each other; and

a circumferential groove (24c) formed on the other of said first peripheral surface and said second peripheral surface;

wherein said guide projection (23c) is engaged in

SUB
A6

said circumferential groove (24c), whereby said drive ring is rotatable about said optical axis relative to said second movable ring and integrally movable with said second movable ring in said optical axis direction.

5 39. The lens barrel according to claim 36, wherein said second movable ring is guided by said stationary barrel to be movable in said optical axis direction without rotating about said optical axis; and

10 wherein said first movable ring is guided by said second movable ring to be movable in said optical axis direction without rotating about said optical axis.

15 40. The lens barrel according to claim 39, wherein said stationary barrel comprises a first linear guide portion (17c) which extends in said optical axis direction;

 wherein said first movable ring comprises a second linear guide portion (11b) which extends in said optical axis direction;

20 wherein said second movable ring comprises:
a first linear guide projection (24a) which extends parallel to said optical axis and is engaged with said first linear guide portion (17c) to guide said second movable ring in said optical axis direction without rotating said second movable ring about said optical axis;
25 and

SUB 7
a second linear guide projection (24b) which extends parallel to said optical axis and is engaged with said second linear guide portion (11b) to guide said first movable ring in said optical axis direction without
5 rotating said first movable ring about said optical axis;

wherein said first linear guide projection (24a) and said second linear guide projection (24b) are formed on an outer peripheral surface of said second movable rings at the same position in a circumferential direction
10 thereof at different positions in said optical axis direction.

41. A lens barrel comprising:

a stationary barrel (16);

20 a hand-operated ring (18) supported by said stationary barrel to be manually rotated;

a lens group (L2) which is movable in a direction of the optical axis thereof;

a lever (22) which is fixed, at one end thereof, to an inner peripheral surface of said hand-operated ring,
20 and wherein the other end of said lever is associated with said lens group, wherein a rotation of said hand-operated ring causes said lens group to move in said optical axis direction via said lever;

a driving gear (20); and

25 an annular gear (21), provided independently of said

hand-operated ring, which meshes with said driving gear,
the center of said annular gear being positioned on said
optical axis;

wherein said annular gear is supported by said
stationary barrel to be rotatable about said optical axis
relative to said stationary barrel;
and

wherein said annular gear and said hand-operated
ring are engaged with each other so as to move integrally
in a circumferential direction of said lens barrel via
said lever.

42. The lens barrel according to claim 41, wherein
said annular gear comprises a radial bottomed groove (21d)
which is formed on a front surface of said annular gear
to extend in a radial direction of said lens barrel, said
front surface facing forward of said optical axis
direction; and

wherein said lever includes a radial portion (22a)
which is engaged in said radial bottomed groove to be
immovable in said circumferential direction relative to
said radial bottomed groove.

43. The lens barrel according to claim 42, wherein
said lever comprises a pair of parallel arms (22b and 22c)
which extend forward from said radial portion of said
lever at different radial positions thereat;

wherein one (22b) of said pair of parallel arms is fixed to said hand-operated ring; and

wherein the other (22c) of said pair of parallel arms is connected to a lens supporting member (12), which supports said lens group, whereby said hand-operated ring is integrally movable with said lens supporting member in a circumferential direction.

44. The lens barrel according to claim 41, wherein said stationary barrel comprises a set of projections (16b) at different positions on said stationary barrel in a circumferential direction about said optical axis; and

wherein said annular gear comprises a corresponding set of circumferential grooves (21c), in which said set of projections are respectively engaged, whereby said annular gear is rotatably supported by said stationary barrel.

45. The lens barrel according to claim 41, wherein said annular gear is molded with synthetic resin.

46. The lens barrel according to claim 41, wherein said lens barrel can be mounted to, and dismounted from, a camera body, said camera body comprising a second driving gear (42) which gives rotation to said driving gear.

47. The lens barrel according to claim 41, wherein

said lens group serves as a focusing lens group, said rotation of said hand-operated ring causing said focusing lens group to move in said optical axis direction via said lever to perform a focusing operation.

5 48. The lens barrel according to claim 47, wherein
SUB A9 }
said lens barrel constitutes a zoom lens barrel, said lens group also serving as a lens group of a zoom lens system, wherein said lens barrel further comprises:

10 a linear moving ring (24) which is guided in said optical axis direction without rotating about said optical axis, said linear moving ring being moved when a zooming operation is performed; and

15 a lens support ring (12) which supports said focusing lens group, and is positioned in said linear moving ring to be supported thereby, so that said lens support ring can be moved in the optical axis direction with respect to said linear moving ring while rotating about said optical axis relative to said linear moving ring;

20 wherein said rotation of said hand-operated ring is transferred to said lens support ring via said lever; and

wherein said lens support ring moves forward and rearward in said optical axis direction relative to said linear moving ring when rotated forwardly and reversely
25 via said lever, respectively.

49. The lens barrel according to claim 41, wherein said lens barrel serves as a zoom lens barrel, said lens group comprising a plurality of movable lens groups serving as a zoom lens system, said rotation of said hand-operated ring causing said plurality of movable lens groups to move in said optical axis direction to vary a focal length.

FULLER